

## TECHNICAL DATA SHEET

**Product Name:** Basketweave 12x24  
**Product Type:** Classic Series Slab

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
<b>Dimensions Metric (mm):</b>	300 x 600 x 45		
<b>Dimensions Imperial (inches):</b>	11.81 x 23.62 x 1.57		
<b>Individual Weight Kg:</b>	18.13		
<b>Individual Weight lbs:</b>	40.00		
<b>Pieces per Bundle</b>	72		
<b>Units per Layer</b>	6		
<b>Bundle Weight Kg</b>	1305.4		
<b>Bundle Weight Lbs</b>	2880.0		
<b>Product Texture:</b>	Slip-resistant surface, intersecting grid pattern. Slight chamfered edge.		

**Product Uses:**

Residential	Commerical			Other			
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>				<input checked="" type="checkbox"/>	

**Physical Parameters**

**Dimensional tolerances:**

Length: -1.0 to 2.0mm  
 Width: -1.0 to 2.0mm  
 Height: +/- 3.00mm

**Flexural Strength:** 5.0 MPa (min)

**Freeze thaw:** A maximum of 225g/m<sup>2</sup> loss of mass after 28 cycles of freezing and thawing or  
 A maximum of 500g/m<sup>2</sup> loss of mass after 49 cycles of freezing and thawing

**Notes:**

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
3. Pedestal set design should be consulted by project specific engineer

*Please contact your Sales Representative for further product information*

## TECHNICAL DATA SHEET

**Product Name:** Basketweave 24x24  
**Product Type:** Classic Series Slab

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
<b>Dimensions Metric (mm):</b>	600 x 600 x 45		
<b>Dimensions Imperial (inches):</b>	23.62 x 23.62 x 1.77		
<b>Individual Weight Kg:</b>	38.00		
<b>Individual Weight lbs:</b>	83.80		
<b>Pieces per Bundle</b>	24		
<b>Units per Layer</b>	2		
<b>Bundle Weight Kg</b>	912.0		
<b>Bundle Weight Lbs</b>	2011.2		
<b>Product Texture:</b>	Slip-resistant surface, intersecting grid pattern. Slight chamfered edge.		

**Product Uses:**

Residential	Commerical				Other		
		Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
Pedestrian <input checked="" type="checkbox"/>	Vehicular	<input checked="" type="checkbox"/>				<input checked="" type="checkbox"/>	

**Physical Parameters**

**Dimensional tolerances:**

Length: -1.0 to 2.0mm  
 Width: -1.0 to 2.0mm  
 Height: +/- 3.00mm

**Flexural Strength:** 5.0 MPa (min)

**Freeze thaw:** A maximum of 225g/m<sup>2</sup> loss of mass after 28 cycles of freezing and thawing or  
 A maximum of 500g/m<sup>2</sup> loss of mass after 49 cycles of freezing and thawing

**Notes:**

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
3. Pedestal set design should be consulted by project specific engineer
4. These products meet the following design guidelines for accessible paths: Slip-resistance surface

***Please contact your Sales Representative for further product information***

## TECHNICAL DATA SHEET

**Product Name:** Basketweave 24x24x50 - Special Order  
**Product Type:** Classic Series Slab

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
<b>Dimensions Metric (mm):</b>	600 x 600 x 50		
<b>Dimensions Imperial (inches):</b>	23.62 x 23.62 x 2		
<b>Individual Weight Kg:</b>	44.27		
<b>Individual Weight lbs:</b>	92.60		
<b>Pieces per Bundle</b>	20		
<b>Units per Layer</b>	2		
<b>Bundle Weight Kg</b>	885.4		
<b>Bundle Weight Lbs</b>	1852.0		
<b>Product Texture:</b>	Slip-resistant surface, intersecting grid pattern. Slight chamfered edge.		

**Product Uses:**

Residential	Commerical				Other		
		Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

**Physical Parameters**

**Dimensional tolerances:**

Length: -1.0 to 2.0mm  
 Width: -1.0 to 2.0mm  
 Height: +/- 3.00mm

**Flexural Strength:** 5.0 MPa (min)

**Freeze thaw:** A maximum of 225g/m<sup>2</sup> loss of mass after 28 cycles of freezing and thawing or  
 A maximum of 500g/m<sup>2</sup> loss of mass after 49 cycles of freezing and thawing

**Notes:**

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
3. Pedestal set design should be consulted by project specific engineer

***Please contact your Sales Representative for further product information***

## TECHNICAL DATA SHEET

**Product Name:** Basketweave 24x24x60 - Special Order  
**Product Type:** Classic Series Slab

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
<b>Dimensions Metric (mm):</b>	600 x 600 x 60		
<b>Dimensions Imperial (inches):</b>	23.62 x 23.62 x 2.36		
<b>Individual Weight Kg:</b>	49.29		
<b>Individual Weight lbs:</b>	108.67		
<b>Pieces per Bundle</b>	18		
<b>Units per Layer</b>	2		
<b>Bundle Weight Kg</b>	887.2		
<b>Bundle Weight Lbs</b>	1956.0		
<b>Product Texture:</b>	Slip-resistant surface, intersecting grid pattern. Slight chamfered edge.		

**Product Uses:**

Residential	Commerical			Other			
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>				<input checked="" type="checkbox"/>	

**Physical Parameters**

**Dimensional tolerances:**

Length: -1.0 to 2.0mm  
 Width: -1.0 to 2.0mm  
 Height: +/- 3.00mm

**Flexural Strength:** 5.0 MPa (min)

**Freeze thaw:** A maximum of 225g/m<sup>2</sup> loss of mass after 28 cycles of freezing and thawing or  
 A maximum of 500g/m<sup>2</sup> loss of mass after 49 cycles of freezing and thawing

**Notes:**

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
3. Pedestal set design should be consulted by project specific engineer

***Please contact your Sales Representative for further product information***

## TECHNICAL DATA SHEET

**Product Name:** Basketweave 24x30  
**Product Type:** Classic Series Slab

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
<b>Dimensions Metric (mm):</b>	600 x 750 x 45		
<b>Dimensions Imperial (inches):</b>	23.62 x 29.52 x 1.77		
<b>Individual Weight Kg:</b>	48.00		
<b>Individual Weight lbs:</b>	105.82		
<b>Pieces per Bundle</b>	24		
<b>Units per Layer</b>	2		
<b>Bundle Weight Kg</b>	1152.0		
<b>Bundle Weight Lbs</b>	2539.7		
<b>Product Texture:</b>	Slip-resistant surface, intersecting grid pattern. Slight chamfered edge.		

**Product Uses:**

Residential	Commerical				Other		
		Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

**Physical Parameters**

**Dimensional tolerances:**

Length: -1.0 to 2.0mm  
 Width: -1.0 to 2.0mm  
 Height: +/- 3.00mm

**Flexural Strength:** 5.0 MPa (min)

**Freeze thaw:** A maximum of 225g/m<sup>2</sup> loss of mass after 28 cycles of freezing and thawing or  
 A maximum of 500g/m<sup>2</sup> loss of mass after 49 cycles of freezing and thawing

**Notes:**

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
3. Pedestal set design should be consulted by project specific engineer

***Please contact your Sales Representative for further product information***