

## TECHNICAL DATA SHEET

Product Name: **Barollo Round Edge 8"**  
 Product Type: Caps

<u>Product Specifications</u>	Width x Height x Depth	Width x Height x Depth	Width x Height x Depth
Dimensions Metric (mm):	200 x 317 x 75		
Dimensions Imperial (inches):	7.87 x 12.46 x 2.95		
Individual Weight Kg:	9.98		
Individual Weight lbs:	22.00		
Pieces per Bundle	90		
Units per Layer			
Bundle Weight Kg	898		
Bundle Weight Lbs	1980.00		
Product Texture:			

**Product Uses:**

Residential	Commerical
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

**Physical Parameters**

**Dimensional tolerances:**

Length: +/- 3.0mm  
 Width: +/- 3.0mm  
 Height: +/- 3.0mm

**Compressive Strength:** 20.7 MPa (min)

**Water Absorption:** 208 kg/m<sup>3</sup>  
 (13 lb/ft<sup>3</sup>)

**Freeze thaw:** after 100 cycles 1% (max)  
 after 150 cycles 1.5% (max)

**Notes:**

1. Meets the requirments for ASTM C1372 - Standard Specifications for Segmental Retaining Wall Units
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

***Please contact your Sales Representative for further product information***

## TECHNICAL DATA SHEET

Product Name: Barollo Round Edge 10"  
 Product Type: Caps

<u>Product Specifications</u>	Width x Height x Depth	Width x Height x Depth	Width x Height x Depth
Dimensions Metric (mm):	250 x 317 x 75		
Dimensions Imperial (inches):	9.84 x 12.46 x 2.95		
Individual Weight Kg:	11.96		
Individual Weight lbs:	26.37		
Pieces per Bundle	81		
Units per Layer			
Bundle Weight Kg	968.86		
Bundle Weight Lbs	2136.00		
Product Texture:			

**Product Uses:**

Residential	Commerical
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

**Physical Parameters**

**Dimensional tolerances:**

Length: +/- 3.0mm  
 Width: +/- 3.0mm  
 Height: +/- 3.0mm

**Compressive Strength:** 20.7 MPa (min)

**Water Absorption:** 208 kg/m<sup>3</sup>  
 (13 lb/ft<sup>3</sup>)

**Freeze thaw:** after 100 cycles 1% (max)  
 after 150 cycles 1.5% (max)

**Notes:**

1. Meets the requirments for ASTM C1372 - Standard Specifications for Segmental Retaining Wall Units
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

*Please contact your Sales Representative for further product information*