

TECHNICAL DATA SHEET

Product Name: Chimney Caps
Product Type: Masonry & Builder

	9X9	9X13	U-CAP	STRINGER
Product Specifications	Width x Depth x Height	Width x Depth x Height	Width x Depth x Height	Width x Depth x Height
Dimensions Metric (mm):	225 x 225 x 75	225 x 330 x 75	226 x 330 x 75	394 x 140 x 2.95
Dimensions Imperial (inches):	8.86 x 8.86 x 2.95	8.86 x 13 x 2.95	8.86 x 13 x 2.96	15.5 x 5.5 x 2.95
Individual Weight Kg:	30.25	33.88	25.58	8.54
Individual Weight lbs:	66.70	74.70	56.40	18.83
Pieces per Bundle	20	20	20	96
Units per Layer				
Bundle Weight Kg	605.09	677.67	511.65	820
Bundle Weight Lbs	1334.00	1494	1128	1808
Product Texture:				

Product Uses:

Residential	Commerical
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Dimensional tolerances:

Length: +/- 3.0mm
 Width: +/- 3.0mm
 Height: +/- 3.0mm

Compressive Strength: 20.7 MPa (min)

Water Absorption: 208 kg/m³
 (13 lb/ft³)

Freeze thaw: after 100 cycles 1% (max)
 after 150 cycles 1.5% (max)

Notes:

Notes:

1. Meets and exceeds the requirements of the CSA 165.2-14 for a Solid Grade I-25 brick. And are in accordance for ASTM Standard C140
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

Please contact your Sales Representative for further product information